CAPLIN

DS4C 6.2

DataSource For C Configuration Syntax Reference

August 2014



Contents

1	Prefa	ce	1
	1.1	What this document contains.	1
		About Caplin document formats	1
	1.2	Who should read this document	1
	1.3	Related documents	1
	1.4	Typographical conventions.	1
	1.5	Feedback	2
	1.6	Acknowledgments	3
2	Introd	duction	4
3	Types	s of configuration item	5
	3.1	Boolean configuration items	5
	3.2	Single value configuration items	5
	3.3	Multi value configuration items	6
	3.4	Configuration items with nested options	6
	3.5	Lists	8
4	Confi	guration Variables	9
	4.1	Defined variables	9
		Using complex expressions to define a variable	10
	4.2	Environment variables	11
5	Cond	itional flow control	12
	5.1	Simple conditional statements	13
	5.2	Complex conditional statements	14
6	Obtai	ning configuration from a webserver	16
7	Appe	ndix: Supported mathematical operators	17
8	Gloss	sary of terms and acronyms	18

1 Preface

1.1 What this document contains

This document describes the syntax of the language that is used to configure DataSource applications that have been built using Caplin's DataSource for C API. Such applications include Caplin Liberator, Caplin Transformer, and Integration Adapters that use the API.

About Caplin document formats

This document is supplied in two formats:

- Portable document format (.PDF file), which you can read on-line using a suitable PDF reader such as Adobe Reader®. This version of the document is formatted as a printable manual; you can print it from the PDF reader.
- Web pages (.HTML files), which you can read on-line using a web browser. To read the web version of the document, navigate to the HTMLDoc folder and open the file index.html.

For the best reading experience

On the machine where your browser or PDF reader runs, install the following Microsoft Windows® fonts: Arial, Courier New, Times New Roman, Tahoma. You must have a suitable Microsoft license to use these fonts.

1.2 Who should read this document

This document is intended for System Administrators who need to install, configure, and manage DataSource for C applications. DataSource for C applications included Caplin Liberator, Caplin Transformer, and Integration Adapters that use the API.

1.3 Related documents

Caplin DataSource Overview

A technical overview of Caplin DataSource.

DataSource for C API Documentation

The API reference documentation that allows application developers to write DataSource for C applications.

1.4 Typographical conventions

The following typographical conventions are used to identify particular elements within the text.

Type Uses

aMethod Function or method name

aParameter Parameter or variable name

/AFolder/Afile.txt File names, folders and directories

Some code; Program output and code examples

The value=10 attribute is... Code fragment in line with normal text

Some text in a dialog box Dialog box output

Something typed in User input – things you type at the computer keyboard

Glossary term Items that appear in the "Glossary of terms and acronyms"

XYZ Product Overview Document name

Information bullet point

Action bullet point – an action you should perform

Note: Important Notes are enclosed within a box like this.

Please pay particular attention to these points to ensure proper configuration and operation of the solution.

Tip: Useful information is enclosed within a box like this.

Use these points to find out where to get more help on a topic.

Information about the applicability of a section is enclosed in a box like this. For example: "This section only applies to version 1.3 of the product."

1.5 Feedback

Customer feedback can only improve the quality of our product documentation, and we would welcome any comments, criticisms or suggestions you may have regarding this document.

Visit our feedback web page at https://support.caplin.com/documentfeedback/.

1.6 Acknowledgments

Adobe® Reader is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries.

Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

Sun and Solaris are trademarks or registered trademarks of Oracle® Corporation in the U.S. and other countries.

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

2 Introduction

DataSource for C applications can be configured by settings stored in one or more configuration files, or by settings stored in a database and supplied to the DataSource application by a configuration script.

This document describes:

- The syntax of the different types of configuration item used to configure a DataSource for C application.
- How variables and conditionals can be used in a configuration file.
- How configuration settings supplied by a web server or configuration script can be used to configure a DataSource for C application.

For a description of the configuration items that you can use to configure a particular DataSource for C application (such as Caplin Liberator, Caplin Transformer or an Integration Adapter), refer the Administration Guide for the application that you want to configure. For a description of the DataSource communications infrastructure and how it links Caplin components together, see the Caplin DataSource Overview document.

3 Types of configuration item

Four different types of configuration item can be used to configure a DataSource for C application:

- Boolean configuration items 5
- Single value configuration items 5
- Multi value configuration items 6
- Configuration items with nested options 6

Some of these configuration items allow you to specify a list of one or more values (see Lists 8).

3.1 Boolean configuration items

A boolean configuration item does not take any value, but is set to true if present in the DataSource configuration, and to false (the default) if omitted from the configuration. An example of a boolean configuration item is **latency-chain-enable**, which enables or disables latency chaining.

Example

latency-chain-enable

In this case latency chaining is enabled.

In the reference sections of the Administration Guide for the DataSource application, the syntax definition specifies further information about boolean configuration items, as shown in the following table.

Туре	Default	Permitted values
boolean	false	True or false, and a description of the effect of each value (such as true to enable or false to disable).

3.2 Single value configuration items

Single value configuration items set something to a single value. An example of this type of configuration item is **datasrc-port**, which specifies the network port that the application listens on for DataSource messages and connection requests.

Example

datasrc-port 22001

In this case the listening port is set to 22001.

If present in the configuration file, a single value configuration item must define the value to be assigned. If not present in the configuration file, the configuration item is assigned a default value.

In the reference sections of the Administration Guide for the DataSource application, the syntax definition specifies further information about single value configuration items, as shown in the following table.

Туре	Default	Permitted values
The type of value, such as string or integer.	The default value, or <no default=""> if there is no default value.</no>	Restrictions on the permitted values for this configuration item.

3.3 Multi value configuration items

Multi value configuration items set the value of two or more related items. An example of this type of configuration item is **add-field**, which maps a field name (a string) to a field number (an integer).

Example

add-field Bid 22

In this case the Bid field is mapped to field number 22.

If a multi value configuration item is present in the configuration file, values must be defined for all related items that are not optional (such as the field name and field number in the example above). If a related item is described as optional in the Administration Guide (such as optional field flags data), the value for that related item can be omitted from the configuration. Values are assigned according to the position of the value in the list of ordered values. If the configuration item is not present in the configuration file, related items are assigned default values.

In the reference sections of the Administration Guide for the DataSource application, named position indicators in the syntax definition indicate how values of related items must be ordered. In the example **add-field** configuration item above, the syntax would look something like this.

Example Syntax for the add-field configuration item

add-field FieldName FieldNumber

Further information about the items that these named position indicators represent are shown in a table like this.

Options

Name	Туре	Default	Description
The name of the position indicator, such as FieldName.	The type of value, such as string or integer.	The default value, or <no default=""> if there is no default value.</no>	Describes the item represented by the named position indicator, and defines any restrictions on its value.

3.4 Configuration items with nested options

This type of configuration item takes nested options, where each nested option can be any one of the four types of configuration item (boolean, single value, multi value, and nested). An example of this type of configuration item is **add-peer**, which specifies options for connecting to a remote DataSource application (a **DataSource peer**).

Example

```
add-peer
addr liberator.example.com
port 25000
end-peer
```

In this case the address of the remote DataSource is set to <code>liberator.example.com</code>, and the port that it listens on to <code>25000</code>.

In the reference sections of the Administration Guide for the DataSource application, the syntax definition specifies the configuration items that can be nested. In the example **add-peer** configuration item above, the syntax would look something like this.

Example Syntax for the add-peer configuration item

```
add-peer
addr <value>
port <value>
end-peer
```

This syntax indicates that if the **addr** and **port** configuration items are present in the configuration, then a value must be defined for each of these items. The angle brackets indicate that <value> is only a place holder for the value, and not the value itself.

The next example shows the syntax for other types of nested configuration item.

Syntax for nested configuration items

```
add-something
boolean-type
single-value-type
multi-value-type
end-something

something
```

The syntax shows that the **add-something** configuration item has three nested options, each type identified by the values they take:

boolean-type Set to true if present in the configuration, otherwise false.

single-value-type Sets a single value if present in the configuration, otherwise takes a default value.multi-value-type Sets multiple values if present in the configuration, otherwise takes default values.

3.5 Lists

Some configuration items allow you to specify a list of one or more values, where each value is the same type. An example is **addr**, which defines a list of addresses that the DataSource application will attempt to connect to.

In the reference sections of the Administration Guide for the DataSource application, the syntax definition specifies the types that can be listed, as shown in the following table.

List Type	Description	Example
string list	A space separated list (array) of one or more strings.	A space separated list of IP addresses. 127.0.0.0 192.255.129.1
integer list	A space separated list (array) of one or more integers.	A space separated list of port numbers. 22001 22002

4 Configuration Variables

Two kinds of variable can be used to configure a DataSource for C application: defined variables and environment variables.

4.1 Defined variables

A configuration variable is defined using the **define** configuration directive, and undefined using the **undefine** directive.

Notation: defining and undefining a variable

define VARIABLE value

undefine VARTABLE

In the notation shown above, VARIABLE is the name of the variable and value is the value that it takes. The name of the variable can contain alphanumeric characters and the characters "." and "_" (without the quotation marks), and by convention is always uppercase. If value is a string that contains spaces, the string must be enclosed in single or double quotation marks.

The following notation shows how a variable is used to set the value of a configuration item.

Notation: using a variable in the configuration

config-item \${VARIABLE}

In the notation shown above, **config-item** is the name of the configuration item, and VARIABLE is the name of the variable that sets the value of the configuration item.

When a variable is used to set the value of a configuration item, the name of the variable must be enclosed in curly braces and preceded by the \$ character. If an undefined variable is used in the configuration, the value of the configuration item is set to an empty string and a warning is logged to the console and log file.

The following example defines a variable, and sets the value of a configuration item using that variable.

Example: defining and using a variable

```
define HTTP_PORT 8080
```

http-port \${HTTP_PORT}

In this case, the value of the http-port configuration item is set to 8080 (using the HTTP PORT variable).

Variables can also be concatenated with surrounding text and other variables.

Example: concatenating a variable with surrounding text

http-port 1\${HTTP_PORT}

In this case, the value of the http-port configuration item is set to 18080.

Pre-defined Variables

The following variables are pre-defined by the **DataSource for C library**:

Pre-defined variables

Name	Description
APP_NAME	The name of the DataSource for C application. Examples are transformer and rttpd.
CPU	The type of processor. Examples are 1686 and sparc.
HOME_DIR	The home directory of the process owner.
HOST_NAME	The name of the host machine.
MAJOR_VERSION	The major version of the DataSource for C library (for example, 5)
MINOR_VERSION	The minor version of the DataSource for C library (for example, 0)
os	The name of the operating system that the DataSource for C library was built for. Examples are linux-gnu and solaris2.10.
OS_TRIPLET	The GNU configuration triplet (of the form cpu-manufacturer-operating_system). Examples are i686-pc-linux-gnu and sparc-sun-solaris2.10.

Using complex expressions to define a variable

Configuration variables can be defined using complex expressions that are evaluated by an arithmetic expressions calculator. The expressions calculator is invoked using the following notation:

Notation to invoke the expressions calculator

\${EVAL:expression}

In the notation shown above, expression is a list of items and arithmetic operators that the expressions calculator evaluates. Each item in expression must have a numeric value, and the valid arithmetic operators are + (addition), - (subtraction), / (division), and * (multiplication). Parenthesis can also be used to group parts of an expression (see Appendix: Supported mathematical operators operator precedence).

The following example uses the expressions calculator to add 80 to the value of the defined variable PORT BASE.

Expressions calculator: setting a port number

```
define PORT_BASE 20000
http-port ${EVAL:${PORT_BASE} + 80}
```

In this case the expression evaluated is \${PORT_BASE} + 80. Because PORT_BASE has the value 20000, the http-port configuration item (the HTTP port number) is set to 20080.

The @ operator allows a configuration item to be used inside an expression. The next example sets the HTTP port number to 8080, and then uses this setting to calculate and set the HTTPS port number.

Expressions calculator: evaluating a configuration item

```
http-port 8080
https-port ${EVAL:@http-port + 1}
```

In this case **http-port** (the HTTP port number) is set to 8080, and **https-port** (the HTTPS port number) is set to 8081.

4.2 Environment variables

Environment variables can be used to set the value of a configuration item.

Notation: using an environment variable in the configuration

```
config-item ${ENV:VARIABLE}
```

In the notation shown above, **config-item** is the name of the configuration item and VARIABLE is the name of the environment variable that sets the value of the configuration item.

The name of the environment variable must be preceded by the text ENV: and enclosed in curly braces, and the braces must be preceded by the \$ character. If the environment variable has not been defined, the value of the configuration item is set to an empty string and a warning is logged to the console and log file.

The following example sets the value of a configuration item using an environment variable.

Example: defining and using an environment variable

```
runtime-user ${ENV:USER}
```

In this case, the value of runtime-user is set to the value of the USER environment variable.

5 Conditional flow control

DataSource for C libraries support conditional flow control constructions that have if/else/elseif/endif statements in the DataSource configuration.

Flow control construction

```
if condition1
...configuration 1
elseif condition2
...configuration 2
else
...configuration 3
endif
```

In the notation shown above, condition1 and condition2 are conditions that evaluate to true or false.

- If condition1 evaluates to true, configuration 1 is applied, otherwise the elseif condition is tested.
- If the elseif condition is tested and condition2 evaluates to true, configuration 2 is applied.
- If condition1 and condition2 evaluate to false, configuration 3 is applied.

The elseif and else statements are optional and the endif statement ends the conditional flow control. There can be more than one elseif statement inside an if/endif construct, but only one else statement.

Each condition can have a simple or complex form, depending on whether the condition is part of a simple or complex conditional statement.

5.1 Simple conditional statements

A simple conditional statement is shown below.

Simple conditional statement

if test value

In a simple conditional statement, test is a data item to test and value is the value to test against. By default, the following data items can be tested:

Data items available to test

Name	Description
application	The name of the application (set using the application-name configuration item).
hostname	The name of the host machine.
os	The name of the running operating system (such as linux-gnu, linux-EL5-gnu, and solaris2.10).

A DataSource for C application can specify other data items to test (see **ds_config_set_test()** in the **DataSource for C API Documentation**), but no Caplin products do so.

Example

The following example sets http-port to 8080 if the application is rttp, and to 8082 otherwise.

Example of a simple conditional statement

```
if application rttp
http-port 8080
else
http-port 8082
endif
```

5.2 Complex conditional statements

A complex conditional statement is shown below.

Conditional statement (complex form)

```
if test operator value
```

In a complex conditional statement, test is a data item to test, value is the value to test against, and operator is a comparison operator used to evaluate the condition.

The following operators (shown separated by commas) can be used inside a complex conditional flow control statement (see Appendix: Supported mathematical operators 17) for further information):

- Arithmetic operators: *, -, /, +
- ◆ Comparison operators: <, >, >=, <=, ==, !=</p>
- Parenthesis: ()
- ◆ Logical operators: and, &&, or, | |
- The @ operator identifies a configuration item.

If value is a string that contains spaces, the string must be enclosed in single or double quotation marks. This means that the following if statements are equivalent:

```
if ${HOST_NAME} == "myserver"
if ${HOST_NAME} == 'myserver'
if ${HOST_NAME} == myserver
```

Conditions that evaluate to 0 are false, and conditions that evaluate to any other number are true. Conditions that evaluate to a string are false.

Examples

The @ operator allows a configuration item to be used in a complex conditional statement.

Example: using the @ operator

```
if @http-port == 80
  https-port 443
endif
```

In this case the https-port is only set to 443 if the http-port is set to 80.

The @ operator can also be used with a boolean configuration item to construct the condition that is evaluated.

Example: using the @ operator with a boolean configuration item

```
if @https-enable
https-port 443
endif
```

In this case the **https-port** is only set if HTTPS enabled (that is, if the boolean configuration item **https-enable** evaluates to true).

The next example shows how logical operators can be used to combine conditions in a flow control statement.

Example: combining conditions using logical operators

```
if ${HTTPS} == 1 and ${HOST_NAME} == myserver
  https-enable
  https-port 443
endif
```

In this case the configuration between the if and endif statements is only applied if the configuration variable HTTP is set to 1 and the configuration variable HOST NAME is set to myserver.

6 Obtaining configuration from a webserver

The configuration for a DataSource for C application can be obtained from a web server by specifying the URL of the required configuration file in an **include-file** directive.

Specifying the URL of a configuration file

```
include-file http://configurationserver/rttpd.conf
```

The example above specifies that configuration in the file rttpd.conf can be obtained from the web server with the domain name configurationserver using the http protocol. Note that the protocol must be HTTP. If a retrieval utility is not specified in the configuration that contains the **include-file** directive, **wget** is used to retrieve the configuration.

A retrieval utility can be specified using the **http-download-command** directive or as part of the **include-file** directive. In either case the specified utility must send the configuration data to **standard output** (**stdout**).

The following example sets **wget** as the retrieval utility (the default utility if the **http-download-command** directive is omitted).

Obtaining a configuration using wget

```
http-download-command "wget -nv -0 -"
include-file http://configurationserver/rttpd.conf
```

The next example sets **curl** as the retrieval utility.

Setting curl as the retrieval utility

```
http-download-command "curl -s"
include-file http://configurationserver/rttpd.conf
```

7 Appendix: Supported mathematical operators

The following mathematical operators can be used in a conditional flow control statement.

The operators are listed in order of precedence (operators at the top of the table have higher precedence than operators at the bottom of the table).

Supported operators (in order of precedence)

Operators	Description
()	Parenthesis (grouping).
* /	Multiplication and division.
+ -	Addition and subtraction
< <= > >=	Comparisons: less than, less than or equal to, more than, more than or equal to.
== !=	Comparisons: equal to, not equal to.
&& and	Logical AND (ձձ or and can be used).
or	Logical OR (or or can be used).

The following table shows some examples of operator use and precedence:

Operator use and precedence

Example	Comment
2 + 3 * 3 = 11	Multiplication is completed before addition.
(2 + 3) * 3 = 15	The operation in parenthesis is completed before the multiplication.
if \${HTTPS} == 1 && \${HOST_NAME} == myserver	True if the variable HTTPS is set to 1 and the variable HOST_NAME is set to myserver.
<pre>if \${HTTPS} == 1 or \${HOST_NAME} == myserver</pre>	True if the variable HTTPS is set to 1 or the variable HOST_NAME is set to myserver.

For a description of the flow control constructions you can use to configure a DataSource for C application, see Conditional flow control 12.

8 Glossary of terms and acronyms

This section contains a glossary of terms, abbreviations, and acronyms used in this document.

Term	Definition
Caplin Liberator	A financial internet hub that delivers data and messages in real time to and from subscribers over any network.
Caplin Platform	An integrated suite of software that supports the services and distribution capabilities needed for web trading. It consists of Caplin Liberator , Caplin Transformer , Caplin KeyMaster, Caplin Director, and Caplin Management Console.
Caplin Transformer	An event-driven, real-time data transformation engine optimized for web trading services.
Configuration file	A file containing the initial settings for a software application.
Configuration item	An entry in a configuration file that holds the value of one or more application settings (see <u>Types of configuration item</u> 5).
CPP	A preprocessor for the C language.
Integration Adapter	A server application that allows an external system to communicate with the Caplin Platform. An Integration Adapter is a DataSource application.
DataSource application	An application that uses the DataSource API.
	Caplin Liberator, Caplin Transformer, and Integration Adapters are all DataSource applications.
DataSource for C application	A DataSource application written in the C programming language using the DataSource for C SDK. Caplin Liberator, Caplin Transformer, and some Integration Adapters are DataSource for C applications.
DataSource for C API	The API provided by the DataSource for C Library.
DataSource for C Library	A software library that allows a DataSource for C application to send messages to other DataSource applications .
DataSource for C SDK	A software development kit that allows you to build custom DataSource for C applications.
DataSource peer	A remote DataSource application that is connected to this DataSource application.
GNU	A project launched in 1984 to develop a Unix-like operating system.



Contact Us

Caplin Systems Ltd Cutlers Court 115 Houndsditch

London EC3A 7BR Telephone: +44 20 7826 9600

www.caplin.com

The information contained in this publication is subject to UK, US and international copyright laws and treaties and all rights are reserved.

No part of this publication may be reproduced or transmitted in any form or by any means without the written authorization of an Officer of Caplin Systems Limited.

Various Caplin technologies described in this document are the subject of patent applications. All trademarks, company names, logos and service marks/names ("Marks") displayed in this publication are the property of Caplin or other third parties and may be registered trademarks. You are not permitted to use any Mark without the prior written consent of Caplin or the owner of that Mark.

This publication is provided "as is" without warranty of any kind, either express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, or non-infringement.

This publication could include technical inaccuracies or typographical errors and is subject to change without notice. Changes are periodically added to the information herein; these changes will be incorporated in new editions of this publication. Caplin Systems Limited may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time.

This publication may contain links to third-party web sites; Caplin Systems Limited is not responsible for the content of such sites.